



SUPREME
Smart Innovation

Power Up, Even When the Lights Go Out



PREMIUM SERIES
**UNINTERRUPTIBLE
POWER SUPPLY**

(1kVA ~ 3kVA)

SPM9110RT

www.supremepowersystems.com

SPM9110RT - RACKMOUNT, ONLINE UPS (1:1)

1kVA ~ 3kVA



Features

- High frequency on-line double conversion technology
- DSP (Digital signal processors) control technology
- Active power factor correction (APFC), input power factor up to 0.99
- Output power factor 0.9
- Wide input voltage range (110 V ~ 300 Vac) and frequency range (40 ~ 70 Hz)
- Auto sensing frequency
- 50 / 60Hz frequency conversion
- Cold start
- Rear ventilation design and variable speed fan
- Effective software and hardware protection
- Quick and stable charging, 90% capacity restored in 4 h (standard model UPS)
- Linear derating in low voltage input reducing battery discharging times
- Settable delayed start when power is restored
- Hot-swappable battery
- Advanced battery management (ABM)
- Multiple functions settable via LCD: output voltage, EOD, auto-start, bypass mode, ECO mode and frequency conversion mode
- Multi-platform communications: RS232 (standard), USB / RS485 / SNMP / dry contacts (optional)
- Optional USB, RS485 card, AS400 dry contacts, SNMP card, SMS alarms, EPO function, MBS (External maintenance bypass switch)

MODEL	SPM9101RT			SPM9102RT			SPM9103RT		
Capacity	1 kVA / 900 W			2 kVA / 1800 W			3 kVA / 2700 W		
INPUT									
Rated voltage	208 / 220 / 230 / 240 Vac								
Voltage range	110 ~ 176 Vac (linear derating between 50% and 100% load); 176 ~ 280 Vac (no derating); 280 ~ 300 Vac (derating 50%)								
Frequency	40 ~ 70 Hz (auto-sensing)								
Power factor	≥ 0.99								
Bypass voltage range	- 25% ~ + 15% settable								
Total harmonic distortion	≤ 6%								
OUTPUT									
Voltage	208 / 220 / 230 / 240 Vac (settable via LCD)								
Voltage regulation	± 1%								
Frequency	45 ~ 55 Hz or 55 ~ 65 Hz (synchronized range); 50 / 60 Hz ± 0.1 Hz (battery mode)								
Waveform	Sinusoidal								
Power factor	0.9								
Total harmonic distortion (THDV)	≤ 2% (linear load), ≤ 5% (non-linear load)								
Crest factor	3:1								
Overload	105% ~ 125% for 1 min, 125% ~ 150% for 30 s, > 150% for 300 ms								
BATTERIES									
DC voltage	24 V (S)	36 V (S)	36 V (H)	48 V (H)	72 V (S)	72 V (S)	72 V (H)	96 V (S)	96 V (H)
Inbuilt battery	2 x 9 Ah	3 x 7 Ah	/	4 x 9 Ah	6 x 7 Ah	/	6 x 9 Ah	8 x 7 Ah	/
Charging current (max.)	1A		6A	1A		6 A	1 A		6 A
Recharge time	Standard model: 90% capacity restored in 3 hours; Long time model: depend on the capacity of battery								
SYSTEM									
Efficiency	≥ 90% (Mains mode) ≥ 85% (Battery mode) ≥ 95% (ECO mode)			≥ 91% (Mains mode) ≥ 86% (Battery mode) ≥ 96% (ECO mode)			≥ 92% (Mains mode) ≥ 87% (Battery mode) ≥ 97% (ECO mode)		
Transfer time	Mains mode to battery mode: 0 ms Inverter mode to bypass mode: 4 ms (typical)								
Protections	Short-circuit, overload, overtemperature, battery discharge protection and fan testing protection								
Communications	RS232 (standard), USB / RS485 / dry contacts / SNMP (optional)								
Display	LCD + LED								
Standards	EN 62040-1, EN 62040-2, EN 61000-3-2, EN 61000-3-3, IEC 61000-4-2, IEC 61000-4-3, IEC 61000-4-4, IEC 61000-4-5, IEC 61000-4-6, IEC 61000-4-8, IEC 61000-4-11, IEC 61000-2-2, IEC 62040-2, IEC 62040-1								
OTHERS									
Operating temperature	0°C ~ 40°C								
Storage temperature	- 25 ~ 55°C (without batteries)								
Relative humidity	0 ~ 95% (non-condensing)								
Altitude	≤ 1000 m, derating 1% for each additional 100 m								
IP rating	IP 20								
Noise level at 1m	≤ 50 dB								
Dimensions (W × D × H) (mm)	440 x 338 x 88	440 x 430 x 88	440 x 468 x 88	440 x 430 x 88	440 x 560 x 88	440 x 468 x 88	440 x 560 x 88	440 x 468 x 88 (UPS) 440 x 468 x 88	440 x 468 x 88
Packaged dimensions (W × D × H) (mm)	545 x 428 x 194	545 x 560 x 201	545 x 592 x 201	545 x 560 x 201	545 x 690 x 201	545 x 592 x 201	545 x 690 x 201	592 x 545 x 198 (UPS) 597 x 545 x 198 (BAT)	545 x 592 x 201
Net weight (kg)	10.6	15.5	7.6	18.7	25.6	9.7	26.8	9.45 (UPS) 27.2 (BAT)	10.1
Gross weight (kg)	11.3	18.6	11.1	21.8	25.8	13.2	29.7	12.97 (UPS) 30.2 (BAT)	13.6

* Derate capacity to 70% in CUCF mode and to 90% when the output voltage is adjusted to 208 Vac

* **S** means standard model, **H** means long time model

* All specifications are subject to change without notice

* Custom-made specifications are acceptable

SPM9100RT



Supreme North America Corporation

13562 Maycrest Way, Richmond, BC, Canada

Tel: +1 604 227 3926 | **Fax:** +1 204 400 8316

Website: www.supremepowersystems.com

